

UNCLASSIFIED

AD NUMBER	
AD338727	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	restricted
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Controlling Organization: British Embassy, 3100 Massachusetts Avenue, NW, Washington, DC 20008.
AUTHORITY	
DSTL, AVIA 18/2045, 30 Jul 2008; DSTL, AVIA 18/2045, 30 Jul 2008	

THIS PAGE IS UNCLASSIFIED

**CONFIDENTIAL**  
MODIFIED HANDLING AUTHORIZED

**AD 338727**

**DEFENSE DOCUMENTATION CENTER**

**FOR**

**SCIENTIFIC AND TECHNICAL INFORMATION**

**CAMERON STATION, ALEXANDRIA, VIRGINIA**



**CONFIDENTIAL**  
MODIFIED HANDLING AUTHORIZED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOTICE:

THIS DOCUMENT CONTAINS INFORMATION  
AFFECTING THE NATIONAL DEFENSE OF  
THE UNITED STATES WITHIN THE MEAN-  
ING OF THE ESPIONAGE LAWS, TITLE 18,  
U.S.C., SECTIONS 793 and 794. THE  
TRANSMISSION OR THE REVELATION OF  
ITS CONTENTS IN ANY MANNER TO AN  
UNAUTHORIZED PERSON IS PROHIBITED  
BY LAW.

CATALOGUED BY DDC 338727  
AS AD No. 338727

U.S. CONFIDENTIAL - Modified Handling Authorized  
~~RESTRICTED~~ ~~RESTRICTED~~ No. 123456789/Arm.



MINISTRY OF AVIATION

**AEROPLANE AND ARMAMENT  
EXPERIMENTAL ESTABLISHMENT**

BOSCOMBE DOWN

~~RESTRICTED~~ ~~RESTRICTED~~

~~RESTRICTED~~ ~~RESTRICTED~~ [U]

~~RESTRICTED~~ ~~RESTRICTED~~

~~RESTRICTED~~ ~~RESTRICTED~~

THIS INFORMATION IS ENCLOSED ONLY FOR OFFICIAL  
USE BY THE RECIPIENT GOVERNMENT AND SUCH OF ITS  
SUBORDINATES UNDER SEAL OF SECRECY, AS MAY BE  
REQUIRED BY A DEFENCE PROJECT DISCLOSURE TO ANY  
OTHER GOVERNMENT OR RELEASE TO THE PRESS OR IN  
ANY OTHER WAY WOULD BE A BREACH OF THESE  
CONDITIONS.

THE INFORMATION SHOULD BE safeguarded UNDER  
THE SAME STANDARD AS THAT MAINTAINED BY HER MAJESTY'S  
GOVERNMENT IN THE UNITED KINGDOM.

THE RECIPIENT IS WARNED THAT INFORMATION  
CONTAINED IN THIS DOCUMENT MAY BE SUBJECT TO  
PRIVATELY OWNED RIGHTS.

  
**MINISTRY OF AVIATION**

THIS DOCUMENT IS THE PROPERTY OF H.M. GOVERNMENT AND  
ATTENTION IS CALLED TO THE PENALTIES ATTACHING TO  
ANY INFRINGEMENT OF THE OFFICIAL SECRETS ACT, 1911.

It is intended for the use of the recipient only, and for communication to such persons  
under whom it may require to be safeguarded with the same care as the source of public  
documents. The officers exercising the power of communication are responsible for  
such information is safeguarded with due caution and reserve. Any person who  
the authorized holder, upon releasing possession of this document, by finding  
otherwise, should forward it, together with his name and address in a closed envelope  
to

THE SECRETARY, MINISTRY OF AVIATION, LONDON, W.C.2

Letter postage need not be prepaid: other postage will be refunded. All persons are  
hereby warned that the unauthorized retention or destruction of this document is an  
offence against the Official Secrets Act.

DDC  
338727  
123456789/Arm.

U.S. CONFIDENTIAL - Modified Handling Authorized  
U.K. RESTRICTED

U. S. CONFIDENTIAL  
RESTRICTED  
MODIFIED AUTHORIZED

Report No. AAEE/Tech/234/Arm.

AEROPLANE AND ARMAMENT EXPERIMENTAL ESTABLISHMENT  
BOSCOMBE DOWN

10 MAY 1963

Sea Vixen Mk.1/Scimitar Aircraft

2" Rocket Firing Installation  
Strengthened Nose Fairings

Presented by

Flt. Lt. C. H. Morriss  
Armament Division

A. & A.E.E. Ref: ARM G.3  
M.O.A. Ref: AV/97/018  
Period of Trial: April-October, 1962

Summary

This Report deals with the trials to clear the Improved Strength Nose Fairing (Drg. ND/7577/2) for Service use when fitted to the No.3 Mk.1 Twenty Four Tube 2" R.P. Launcher on Sea Vixen and Scimitar aircraft.

Clearance is recommended for the Improved Strength Nose Fairing for use under the following conditions when fitted to Sea Vixen Mk.1 and Scimitar aircraft:-

Heights up to 45,000 feet

Speeds up to 600 knots

and throughout the full range of manoeuvres within the limitations of the aircraft.

This Report is issued with the authority of

"This document contains information relating to the National Defense of the United States and its contents are prohibited in any manner to be disclosed by law."

Air Commodore,  
Commandant, A. & A.E.E.

List of Contents

	<u>Page</u>
1. Introduction	3
2. Object of Trial	3
3. Description of Installation	3
4. Method of Trial	3
5. Results of Trial	4
6. Conclusions	4
7. Recommendations	4

List of Appendices

	<u>Appendix</u>
Flight Details	I

1. Introduction

Clearance trials of the Improved Strength Nose Fairing for the No.3 Mk.1 Twenty Four Tube 2" R.P. Launcher were requested by the Ministry of Aviation (M.O.A. Trials Proforma AV/97/018 dated 19th March, 1962 refers) prior to its issue for Service use on Sea Vixen Mk.1 and Scimitar aircraft. These trials have been completed.

2. Object of Trial

The object of the trial was to prove the improved strength nose fairings fitted to the No.3 Mk.1 Twenty Four Tube 2" R.P. Launcher throughout the flight envelope of the Sea Vixen Mk.1 aircraft. The fairings were also to be subjected to flight through heavy rain conditions and heavy 'g' loadings. The results of the trials were to apply equally to the use of these fairings on Scimitar aircraft.

3. Description of Installation

A Sea Vixen Mk.1 aircraft was equipped as follows:

- (1) 4 x 24 Tube Launchers No.3 Mk.1 (two per wing on pylons) to which were fitted:-

Inner pylons - improved strength nose fairings

Outer pylons - standard nose fairings.

- (ii) High speed cameras on each wing facing inwards to record destruction of nose fairings, rocket emergence and initial flight path.

- (iii) Forward facing cameras on each wing to record rocket flight path.

A Hunter Mk.6 aircraft used in the initial stages of the trials was equipped as follows:-

- (1) 2 x 24 Tube Launchers No.3 Mk.1 (one per wing on pylons) to which were fitted improved strength nose fairings.

- (ii) High speed cameras in the fuselage facing outwards to record destruction of the nose fairings, rocket emergence and initial flight path.

- (iii) Forward facing cameras in the nose and on the port wing to record rocket flight path.

4. Method of Trial

The improved strength nose fairings were subjected to:-

- (1) 2" Rockets firing through the fairing.
- (ii) Normal flight conditions throughout a full range of heights and speeds (1,000 to 45,000 feet and 200 to 600 knots).
- (iii) Normal handling by ground personnel before, between and after flights.
- (iv) High speed/low level flights through heavy rain.
- (v) Comparison under all conditions (except 'g' loading) with the standard nose fairing.
- (vi) 'g' loading, straight and level, and turns, to 6 'g'.

In addition the 2" Rocket firing flights were carried out using 2" Rockets fitted with the OR.942 fuse.

## 5. Results of Trial

The first five sorties were combined with the air firing of OR.942 fuzeed 2" rockets at heights between 10,000 and 16,000 feet and indicated Airspeeds between 430 and 510 knots. In every case, even when only one rocket was fired, the improved strength nose fairing disintegrated satisfactorily and had no apparent effect on the rocket flight or the operation of the rocket fuze. A further thirteen flights were then made with standard rockets at speeds between 200 and 600 knots I.A.S. at heights between 1,000 and 45,000 feet.

On sortie No.10 the aircraft was flown at 500 knots through heavy thunderstorm rain in order to simulate a tropical rainstorm. The improved strength fairing was unmarked but the standard fairing was badly pitted over its upper surface up to 6 inches back from the nose. The pitting was approximately half an inch in diameter and a quarter of an inch deep.

On sortie No.11 flying at 230 knots at 45,000 feet, normal rain was encountered which caused half inch diameter blisters on the upper surface of the standard nose fairing, but left the improved strength fairing untouched. During sortie No.15, flying at 575 knots I.A.S. and 5,000 feet, the improved strength fairing collapsed and disintegrated approximately 30 seconds after attaining this speed. However, as this fairing had flown on the last eleven sorties, between each of which it was removed, stored and replaced, and had suffered two flights through rain (sortie Nos. 10 and 11) it was considered that there may have been some structural weakening which was not apparent to the eye. Therefore, it is suggested that this failure is not representative of fairings which would not normally be used on more than two flights before being destroyed by firing. This contention is borne out by the fact that on the five subsequent runs at speeds between 594 and 600 knots no failures were experienced.

One flight was made at between 5,000 and 7,000 feet during which the improved nose fairings were subjected to loadings up to 6 'g' during pull-out and from dives and in turns.

After a total of nineteen flights covering speeds between 200 and 600 knots, and at heights between 1,000 and 45,000 feet, it was considered that only flights at speeds in excess of 600 knots would be of any further value, but this Establishment had no aircraft at this time which was capable of performing this task. Therefore, to avoid further delay, the trial was terminated.

## 6. Conclusions

It is concluded that:-

- (i) The Improved Strength Nose Fairing offered better resistance to weathering than did the Standard Fairing, and produced no apparent adverse effects on rocket flight or fuze operation.
- (ii) The Improved Strength Nose Fairing withstood speeds up to 600 knots and 'g' loadings up to 6 'g'.

## 7. Recommendations

It is recommended that this Improved Strength Nose Fairing be cleared for Service use on Sea Vixen Mk.1 and Scimitar aircraft under the following conditions:-

Heights up to 45,000 feet

Speeds up to 600 knots

and throughout the full range of manoeuvres within the limitation of the aircraft.

/Circulation List ...



Circulation List

D.A. Arm.	3 Copies 1 for Action
A.D.P.An.	2 " (for information of D.P.O.)
A.D.P.An.	1 Copy
C.I.S.L.O.	1 "
R.D.T.3	1 "
T.I.L.	70 Copies
R.A.E. Farnborough	5 "
R.A.E. Bedford	2 "
R.T.O. de Havillands	2 "

Flight Details

Sortie No.	Fairings Fitted		Speed (knots)	Height (feet)	2" R.P. Fired	Remarks
	Old	New				
1	-	1	430	10,000	3	No apparent deflection of rockets. Satisfactory disintegration.
2	-	2	480	10,000	3	" " "
3	-	2	430	10,000	2	" " "
4	-	2	510	12,000	3	" " "
5	-	2	500	16,000	3	" " "
6	-	2	450	10,000	2	" " "
7	-	2	450	10,000	1	" " "
8	-	2	450	10,000	3	" " "
9	-	2	450	10,000	3	" " "
6	1	1	250-365	30,000	-	No damage to either fairing.
7	1	1	250-500	5,000	-	" " "
8	1	1	250-500	5,000	-	" " "
9	1	1	250	40,000	-	" " "
10	1	1	225-475	10,000	-	" " "
10	1	1	500	5,000	-	Heavy thunderstorm rain. Improved fairing no damage. Standard fairing badly pitted to depth of $\frac{1}{4}$ inch over upper surface up to 6" back from nose.
11	1	1	230	45,000	-	Standard fairing blistered by rain. Improved fairing no damage.
12	1	1	500	5,000	-	No damage to either fairing.
13	1	1	500	5,000	-	" " "
14	1	1	200-430	20,000	-	" " "
15	1	1	575	5,000	-	Improved fairing collapsed and disintegrated after approximately 30 seconds at this speed.
16		2	594	1,000	-	No damage to either fairing.
17		2	600	1,500	-	" " "
18		2	600	2,000	-	" " "
19		2	600	1,000	-	" " "
19		2	600	1,000	-	" " "
19		2	400	5,000-7,000	-	5 runs pulling, 2s, 3s, 4s, 5s and 6s respectively then 3 turns pulling 6s for 15 seconds each. No damage was suffered.

Flights discontinued as no aircraft available to achieve greater speeds.

**CONFIDENTIAL**  
**MODIFIED HANDLING AUTHORIZED**

**CONFIDENTIAL**  
**MODIFIED HANDLING AUTHORIZED**



*Information Centre  
Knowledge Services*  
**[dstl]** Porton Down,  
Salisbury  
Wiltshire  
SP4 0JQ  
22060-6218  
Tel: 01980-613753  
Fax 01980-613970

Defense Technical Information Center (DTIC)  
8725 John J. Kingman Road, Suit 0944  
Fort Belvoir, VA 22060-6218  
U.S.A.

AD#: AD338727

Date of Search: 30 July 2008

Record Summary: AVIA 18/2045

Title: Sea Vixen Mk I Scimitar aircraft 2" rocket firing installation strengthened nose fairings  
Availability Open Document, Open Description, Normal Closure before FOI Act: 30 years  
Former reference (Department) AAEE/TECH 234/A  
Held by The National Archives, Kew

This document is now available at the National Archives, Kew, Surrey, United Kingdom.

DTIC has checked the National Archives Catalogue website (<http://www.nationalarchives.gov.uk>) and found the document is available and releasable to the public.

Access to UK public records is governed by statute, namely the Public Records Act, 1958, and the Public Records Act, 1967.  
The document has been released under the 30 year rule.  
(The vast majority of records selected for permanent preservation are made available to the public when they are 30 years old. This is commonly referred to as the 30 year rule and was established by the Public Records Act of 1967).

**This document may be treated as UNLIMITED.**